



Moulded Case Circuit Breaker



BH Circuit Breaker



Plug in type

Description: For protection against overload and short circuits in the electrical distribution system. Use in domestic, commercial, light industrial installations.

Specification:

Standard	Conform to IEC 60898
Pole Number (P)	1, 2, 3, 4
Rated Current(A)	10A, 15A, 20A, 30A, 40A, 50A, 60A, 75A, 100A
Rated Voltage(V)	220V/380V
Breaking Capacity	5KA
Frequency	50/60Hz
Body Material	Glassfiber polyester/Bakelite
Installation Method	Clips mounting/Plug in

NVL-50H RCBO



Description: For protection against overload and short circuits in the electrical distribution system. Use in domestic, commercial, light industrial installations.

Specification:

Standard	Conform to IEC 61009
Pole Number (P)	1, 2, 3, 4
Rated Current(A)	10A, 15A, 20A, 30A, 40A, 50A, 60A
Rated Voltage(V)	110V/220V/380V
Breaking Capacity	Icu:5KA/10KA/15KA
Frequency	50/60Hz
Four Adjustable Rated Leakage Currents	30mA/100mA/300mA/500mA
Non-Adjustable Rated Leakage Current	30mA

NVS-50H Leakage Circuit Breaker

Description: For protection against short circuits in the electrical distribution system. Use in domestic , commercial, light industrial installations.



Specification :

Standard	Conform to IEC 61009
Pole Number (P)	2, 3
Rated Current(A)	10A, 15A, 20A, 30A, 40A, 50A
Rated Voltage(V)	110V/220V/380V
Frequency	50/60Hz
Short-time Withstand Current	1500A
Rated Leakage Current	30mA
Body Material	Bakelite

NT 50 Safety Breaker/NT 50 LE

Description: For protection against overload and short circuits in the electrical distribution system. Use in domestic, commercial, light industrial installations.



Specification :

Standard	Conform to IEC 61009
Rated Current(A)	10A, 15A, 20A, 30A
Rated Voltage(V)	110V/220V
Frequency	50/60Hz
Short-time Withstand Current	1500A
Rated Leakage Current	10mA/30mA
Body Material	Glassfiber polyester/Bakelite

IP68 Waterproof Leakage Circuit Breaker

Description: For protection against short circuits in the electrical distribution system. Use in domestic, commercial, light industrial installations.



Specification :

Standard	Conform to IEC 61009
Rated Current(A)	10A, 15A, 20A, 30A
Rated Voltage(V)	110V/220V
Frequency	50/60Hz
Short-time Withstand Current	1500A
Four Adjustable Rated Leakage Currents	30mA/100mA/300mA/500mA
Body Material	Glassfiber polyester/Bakelite

ROCKGRAND GROUP:

WENZHOU ROCKGRAND TRADE CO.,LTD

WENZHOU DAGUAN ELECTRICS CO.,LTD (Factory)

ADD:NO.A1501 XINYI BUILDING SHIFU ROAD WENZHOU CHINA

ADD:ZHEJIANG YONGJIA WUNIU DONGMENG INDUSTRY AREA

Tel:86-577-88670088,88393757,88397206

Fax:86-577-88398508

E-mail:rockgrand@rockgrand.com